Form No.: 002-EN Issue date:15.12.2022 PDS No.: AL/HF-P-0016/01



Product Data Sheet

Aminol[™] Hydraulic HLP 22 Zinc Free

Hydraulic oil

Product description

Aminol[™] Hydraulic HLP 22 Zinc Free is a high-performance zinc-free ashless hydraulic oil designed for top-notch performance in hydraulic systems, power transmission, and general machine lubrication, especially under moderate to severe conditions. It features a formulation with high-quality mineral base stocks and a special additive technology, effectively preventing corrosion, wear, aging, and friction.

Application

- Manufacturing and industrial hydraulic systems
- · Severe-duty hydraulic service
- Marine and mobile hydraulic systems
- High-pressure vane, piston, and gear pumps operating at elevated temperatures
- Systems employing multi-metal designs in system components

Features & Benefits

- Excellent anti-oxidation and anticorrosion properties.
- High thermal-oxidative stability.
- Outstanding seal compatibility.
- Superior antiwear characteristics.
- Great air separation ability.
- Extended oil drain intervals.

Typical Properties

Property	Unit	Test method	Typical value
ISO viscosity grade	-	-	22
Density at 15°C	g/cm3	ASTM D4052	0.866
Kinematic Viscosity at 40°C	mm2/s	ASTM D445	22
Kinematic Viscosity at 100°C	mm2/s	ASTM D445	4.32
Viscosity Index	-	ASTM D2270	100

Form No.: 002-EN Issue date:15.12.2022 PDS No.: AL/HF-P-0016/01



Flash Point (COC)	°C	ASTM D92	170
Pour Point	°C	ASTM D97	-36
Water separability	min	ASTM D7451	10
-time to 3 ml emulsion min	min	ASTM D7451	10
Oxidation Stability after 1000h/TAN increase	min	ASTM D4310	<1
FZG EP Wear Test (A 8.3/90)	-	ASTM D 5182	12
Failure Load Stage	-	ASTM D 5182	12

Typical property characteristics are based on current production. Whilst future production will conform to Aminol[™] specifications, variations in these characteristics may occur.

Performance claims

- DIN 51524-2
- ISO 11158 (HM)
- ASTM D6158 (HM)
- SAE MS 1004
- ISO 20763

Health, Safety & Environment

• Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Safety Data Sheet which can be obtained upon request or through our website: <u>www.aminol.az</u>

• Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Available pack sizes

- 1 L Canister plastic
- 4 L Canister plastic
- 5 L Canister plastic
- 7 L Canister plastic

- 20 L Canister plastic
- 30 L Canister plastic
- 200 L Drum sheet metal
- 1000 L Container

Form No.: 002-EN Issue date:15.12.2022 PDS No.: AL/HF-P-0016/01



Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.

Notes

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.

© 2016-2024 | All rights reserved The logos and trademarks used herein are properties owned by ALCO LLC.

