



Product Data Sheet

Aminol™ ScootForce 2T

Motorcycle oil

Product description

Aminol™ ScootForce 2T is a high-performance, low-smoke 2-stroke engine oil developed specifically for contemporary scooters. It's formulated using carefully chosen base stocks and an advanced additive package, ensuring a consistently smooth and stable ride

Application

Aminol™ ScootForce 2T can be used in air-cooled and water-cooled 2-stroke engines, accommodating both separate and mixed lubrication. During mixed lubrication, it is crucial to observe the specified mixing ratio according to the engine manufacturer's guidelines.

Features & Benefits

- Good corrosion protection
- High wear resistance
- Residue-free combustion
- High thermal stability
- 'Low smoke' formulation
- Reduced deposits on piston rings, outlet ports, and spark plugs
- Multi-functional application possibilities

Typical Properties

Property	Unit	Test method	Typical value
Kinematic Viscosity at 100°C	cst	ASTM D 445	8
Kinematic Viscosity at 40°C	cst	ASTM D 445	62.65
Viscosity Index	-	ASTM D 2270	93
Flash Point, COC	°C	ASTM D 92	224
Pour Point	°C	ASTM D 97	-21
Density at 15°C	g/ml	ASTM D 4052	0.884



Typical property characteristics are based on current production. Whilst future production will conform to Aminol™ specifications, variations in these characteristics may occur.

Performance claims

- API TC
- JASO FD
- ISO L-EGD

Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Safety Data Sheet which can be obtained upon request or through our website: www.aminol.az

- **Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Available pack sizes

- 1 L Canister plastic
- 4 L Canister plastic
- 5 L Canister plastic
- 7 L Canister plastic
- 20 L Canister plastic
- 30 L Canister plastic
- 200 L Drum sheet metal
- 1000 L Container

Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.



Notes

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.