



Product Data Sheet

Aminol™ Special Generation SLG7 10W-30 SP/GF-6A

Engine oil

Product description

Aminol™ Special Generation SLG7 10W-30 SP/GF-6A is a premium quality multi-grade engine oil engineered for exceptional engine protection and outstanding fuel economy, even during extreme driving conditions. It surpasses conventional engine oils by reducing friction and wear during start-up, while also safeguarding the engine against performance-hindering sludge and varnish deposits

Application

Aminol™ Special Generation SLG7 10W-30 SP/GF-6A is suitable for all types of modern gasoline-powered vehicles, including high-performance turbocharged, supercharged, multi-valve fuel-injected engines found in passenger cars, SUVs, light vans, and light trucks where the manufacturer recommends an API SP, ILSAC GF-6, or earlier specification 10W-30 lubricant.

Features & Benefits

- Outstanding thermal and oxidation stability
- Exceptional low temperature capabilities
- Quick cold weather starting
- Exceptional wear protection
- Remarkable resistance to oxidation and foaming
- Excellent dispersive and detergent properties
- Superior fuel economy and CO2 reduction

Typical Properties

Property	Unit	Test method	Typical value
Kinematic Viscosity at 100°C	cst	ASTM D 445	11
Kinematic Viscosity at 40°C	cst	ASTM D 445	67.7
Viscosity Index	-	ASTM D 2270	155
Flash Point, COC	°C	ASTM D 92	230
Pour Point	°C	ASTM D 97	-33



TBN	mg KOH/g	ASTM D 2896	7.2
Sulphated Ash Content	%	ASTM D 874	0.72
Density at 15°C	g/ml	ASTM D 4052	0.847

Typical property characteristics are based on current production. Whilst future production will conform to Aminol™ specifications, variations in these characteristics may occur.

Performance claims

- API SP
- ILSAC GF-6A
- GM 6094M
- Chrysler MS-6395
- Ford WSS-M2C205-A

Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Safety Data Sheet which can be obtained upon request or through our website: www.aminol.az

- **Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Available pack sizes

- 1 L Canister plastic
- 4 L Canister plastic
- 5 L Canister plastic
- 7 L Canister plastic
- 20 L Canister plastic
- 30 L Canister plastic
- 200 L Drum sheet metal
- 1000 L Container

Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.



Notes

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.