Form No.: 002-EN Issue date:15.12.2022 PDS No.: AL/TR-P-0004/01



Product Data Sheet

Aminol™ Turbo EP 32

Turbine oil

Product description

Aminol™ Turbo EP 32 is a premium trubine fluid specifically designed for use in gas turbines and combined cycles operating under severe conditions. Formulated with carefully selected base stocks and additives, it ensures excellent oxidation stability, outstanding anti-foam properties, rapid air release, and exceptionally high demulsibility.

Application

Aminol™ Turbo EP 32 is significantly exceeds the demanding service requirements of gas and steam turbine operators in power generation, prime movers, and other industrial applications. It is primarily recommended for geared heavy-duty gas turbines that require a turbine fluid providing superior wear and scuffing protection

Features & Benefits

- · Exceptional oxidation resistance
- Extra high thermal stability
- Superior anti-wear and extreme-pressure properties
- Robust rust and anti-corrosion performance
- Longer component life
- · Excellent air and water separability

Typical Properties

Property	Unit	Test method	Typical value
ISO viscosity grade	-	-	32
Density at 15°C	g/cm3	ASTM D4052	0.859
Kinematic Viscosity at 40°C	cst	ASTM D445	32.00
Kinematic Viscosity at 100°C	mm2/s	ASTM D445	5.54
Viscosity Index	-	ASTM D2270	109
Flash Point (COC)	°C	ASTM D92	226
Pour Point	°C	ASTM D97	-15

Form No.: 002-EN Issue date:15.12.2022 PDS No.: AL/TR-P-0004/01



Copper Corrosion, 3h, 100°C	-	ASTM D 130	1a
Water separability, sAL	-	ASTM D 7451	30
RBOST test, min.	-	ASTM D 2272	1100
FZG test (Fail Load Stage)	-	DIN 51534 part 2	10
Foaming characteristics, Tendency/ Stability, ml Seq I Seq II Seq III	ml	ASTM D 892	0/0 20/0 0/0

Typical property characteristics are based on current production. Whilst future production will conform to Aminol™ specifications, variations in these characteristics may occur.

Performance claims

- Siemens TLV 9013 04/9013 05
- ALSTOM HTGD 90 117 V0001Y
- GEK 27070/28143B/32568K/46506E
- DIN 51515 Parts I/II
- MORGOIL® Advanced Lubricant New Oil Revision 2.5a
- AIST 120/125
- AGMA 9005-F16
- British Standard BS489

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Safety Data Sheet which can be obtained upon request or through our website: www.aminol.az

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Available pack sizes

- 1 L Canister plastic
- 4 L Canister plastic
- 5 L Canister plastic
- 7 L Canister plastic

- 20 L Canister plastic
- 30 L Canister plastic
- 200 L Drum sheet metal
- 1000 L Container

Form No.: 002-EN Issue date:15.12.2022 PDS No.: AL/TR-P-0004/01



Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.

Notes

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.

© 2016-2024 | All rights reserved

The logos and trademarks used herein are properties owned by ALCO LLC.

